



## ISOMAX - ISO 5599-1 - Sizes 1, 2 & 3

### CNOMO operator with 30 x 30 DIN Form A / 24 Vdc / 2,7 W solenoid

With non locking manual override on solenoid valve operator - Without direct valve spool manual override



| Symbol                                                                             | Description                                                                                                              | Size      | Weight (g) | Order code          |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-----------|------------|---------------------|
|    | 5/2 Single solenoid - Spring return<br> | 1 - 43 mm | 500        | <b>DX1-621-BL49</b> |
|                                                                                    |                                                                                                                          | 2 - 56 mm | 750        | <b>DX2-621-BL49</b> |
|                                                                                    |                                                                                                                          | 3 - 71 mm | 1250       | <b>DX3-621-BL49</b> |
|                                                                                    | 5/2 Single solenoid - Differential<br>  | 1 - 43 mm | 500        | <b>DX1-651-BL49</b> |
|                                                                                    |                                                                                                                          | 2 - 56 mm | 750        | <b>DX2-651-BL49</b> |
|                                                                                    |                                                                                                                          | 3 - 71 mm | 1250       | <b>DX3-651-BL49</b> |
|                                                                                    | 5/2 Double solenoid<br>                 | 1 - 43 mm | 650        | <b>DX1-606-BL49</b> |
|                                                                                    |                                                                                                                          | 2 - 56 mm | 900        | <b>DX2-606-BL49</b> |
|                                                                                    |                                                                                                                          | 3 - 71 mm | 1400       | <b>DX3-606-BL49</b> |
|   | 5/3 Closed Center                                                                                                        | 1 - 43 mm | 560        | <b>DX1-616-BL49</b> |
|                                                                                    |                                                                                                                          | 2 - 56 mm | 900        | <b>DX2-616-BL49</b> |
|                                                                                    |                                                                                                                          | 3 - 71 mm | 1400       | <b>DX3-616-BL49</b> |
|                                                                                    | 5/3 Vented Center<br>                   | 1 - 43 mm | 650        | <b>DX1-611-BL49</b> |
|                                                                                    |                                                                                                                          | 2 - 56 mm | 900        | <b>DX2-611-BL49</b> |
|                                                                                    |                                                                                                                          | 3 - 71 mm | 1400       | <b>DX3-611-BL49</b> |
|  | 5/3 Pressurised Center                                                                                                   | 1 - 43 mm | 650        | <b>DX1-613-BL49</b> |
|                                                                                    |                                                                                                                          | 2 - 56 mm | 900        | <b>DX2-613-BL49</b> |

Solenoid connectors & cable plug to be ordered separately. See solenoid section

## ISOMAX - ISO 5599-1 - Sizes 1, 2 & 3

### CNOMO operator without coil

With non locking manual override on solenoid valve operator - Without direct valve spool manual override

| Symbol                                                                              | Description                                                                                                                | Size      | Weight (g) | Order code        |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-----------|------------|-------------------|
|   | 5/2 Single solenoid - Spring return<br> | 1 - 43 mm | 400        | <b>DX1-621-BN</b> |
|                                                                                     |                                                                                                                            | 2 - 56 mm | 650        | <b>DX2-621-BN</b> |
|                                                                                     |                                                                                                                            | 3 - 71 mm | 1150       | <b>DX3-621-BN</b> |
|                                                                                     | 5/2 Single solenoid - Differential<br>  | 1 - 43 mm | 400        | <b>DX1-651-BN</b> |
|                                                                                     |                                                                                                                            | 2 - 56 mm | 650        | <b>DX2-651-BN</b> |
|                                                                                     |                                                                                                                            | 3 - 71 mm | 1150       | <b>DX3-651-BN</b> |
|                                                                                     | 5/2 Double solenoid<br>                 | 1 - 43 mm | 550        | <b>DX1-606-BN</b> |
|                                                                                     |                                                                                                                            | 2 - 56 mm | 800        | <b>DX2-606-BN</b> |
|                                                                                     |                                                                                                                            | 3 - 71 mm | 1300       | <b>DX3-606-BN</b> |
|  | 5/3 Closed Center                                                                                                          | 1 - 43 mm | 550        | <b>DX1-616-BN</b> |
|                                                                                     |                                                                                                                            | 2 - 56 mm | 800        | <b>DX2-616-BN</b> |
|                                                                                     |                                                                                                                            | 3 - 71 mm | 1300       | <b>DX3-616-BN</b> |
|                                                                                     | 5/3 Vented Center<br>                   | 1 - 43 mm | 550        | <b>DX1-611-BN</b> |
|                                                                                     |                                                                                                                            | 2 - 56 mm | 800        | <b>DX2-611-BN</b> |
|                                                                                     |                                                                                                                            | 3 - 71 mm | 1300       | <b>DX3-611-BN</b> |
|  | 5/3 Pressurised Center                                                                                                     | 1 - 43 mm | 550        | <b>DX1-613-BN</b> |
|                                                                                     |                                                                                                                            | 2 - 56 mm | 800        | <b>DX2-613-BN</b> |

30 x 30 DIN Form A or 22 x 30 DIN Form B coil & coil connectors to be ordered separately. See solenoid section