


**06E Filter / Regulator - Compact**

- Space saving package offers both filter and regulator features for optimal performance
- Excellent water removal efficiency
- Rolling diaphragm for extended life
- Quick response, and accurate pressure regulation regardless of changing flow or inlet pressure
- Two high flow 1/4" gauge ports can be used as additional outlets
- Shown with recommended metal bowl guard
- 1/4", 3/8", 1/2" ports (NPT)

**Operating information**

|                              |      |                                                                  |
|------------------------------|------|------------------------------------------------------------------|
| Supply pressure (max):       |      |                                                                  |
| Plastic bowl                 |      | 0 to 150 psig (0 to 10.3 bar)                                    |
| Metal bowl                   |      | 0 to 250 psig (0 to 17.2 bar)                                    |
| Auto float drain             |      | 15 to 250 psig (1.0 to 17.2 bar)                                 |
| Operating temperature:       |      |                                                                  |
| Plastic bowl                 |      | 32°F to 125°F (0°C to 52°C)                                      |
| Metal bowl                   |      | 32°F to 175°F (0°C to 80°C)                                      |
| Secondary pressure range:    |      |                                                                  |
| Standard                     |      | 2 to 125 psig (0 to 8.6 bar)                                     |
| Low                          |      | 1 to 60 psig (0 to 4.1 bar)                                      |
| High                         |      | 5 to 250 psig (0.4 to 17.2 bar)                                  |
| Flow capacity <sup>†</sup> : |      |                                                                  |
| High flow                    | 1/4" | 45 scfm (21.7 dm³/s, ANR)                                        |
|                              | 3/8" | 55 scfm (26 dm³/s, ANR)                                          |
|                              | 1/2" | 61 scfm (28.8 dm³/s, ANR)                                        |
| Bowl capacity:               |      |                                                                  |
|                              |      | 4.4 oz.                                                          |
| Gauge ports (2):             |      |                                                                  |
|                              |      | 1/4 inch (can be used as additional full flow 1/4" outlet ports) |
| Sump capacity:               |      |                                                                  |
|                              |      | 1.75 oz.                                                         |
| Weight:                      |      |                                                                  |
|                              |      | 1.6 lb (0.7 kg)                                                  |

<sup>†</sup> scfm = Standard cubic feet per minute at 100 psig inlet, 90 psig no flow secondary setting and 10 psig pressure drop.

**Ordering Information:**

| Port Size | Description *                                                                         | Part Number       |
|-----------|---------------------------------------------------------------------------------------|-------------------|
| 1/4"      | Poly Bowl, Metal Guard, Twist Drain, 40 micron, 2-125 psi w/out Gauge, Relieving      | <b>06E12A13AC</b> |
| 1/4"      | Poly Bowl, Metal Guard, Twist Drain, 40 micron, 2-125 psi w/ Gauge, Relieving         | <b>06E12A18AC</b> |
| 1/4"      | Poly Bowl, Metal Guard, Twist Drain, 5 micron, 2-125 psi w/ Gauge, Relieving          | <b>06E12B18AC</b> |
| 1/4"      | Metal Bowl, Twist Drain, 40 micron, 2-125 psi w/out Gauge, Relieving                  | <b>06E13A13AC</b> |
| 1/4"      | Metal Bowl, Twist Drain, 40 micron, 2-125 psi w/out Gauge, T-Handle Relieving         | <b>06E13A13TC</b> |
| 1/4"      | Metal Bowl, Twist Drain, 40 micron, 2-125 psi w/ Gauge, Relieving                     | <b>06E13A18AC</b> |
| 1/4"      | Metal Bowl, Sight Gauge, Twist Drain, 40 micron, 2-125 psi w/out Gauge, Relieving     | <b>06E14A13AC</b> |
| 1/4"      | Metal Bowl, Sight Gauge, Twist Drain, 40 micron, 2-125 psi w/ Gauge, Relieving        | <b>06E14A18AC</b> |
| 1/4"      | Poly Bowl, Metal Guard, Auto Float Drain, 40 micron, 2-125 psi w/out Gauge, Relieving | <b>06E16A13AC</b> |
| 1/4"      | Poly Bowl, Metal Guard, Auto Float Drain, 40 micron, 2-125 psi w/ Gauge, Relieving    | <b>06E16A18AC</b> |
| 3/8"      | Poly Bowl, Metal Guard, Twist Drain, 40 micron, 2-125 psi w/out Gauge, Relieving      | <b>06E22A13AC</b> |
| 3/8"      | Poly Bowl, Metal Guard, Twist Drain, 40 micron, 2-125 psi w/ Gauge, Relieving         | <b>06E22A18AC</b> |
| 3/8"      | Poly Bowl, Metal Guard, Twist Drain, 5 micron, 2-125 psi w/out Gauge, Relieving       | <b>06E22B13AC</b> |

*Continued on next page*

**Most popular.**

