


## 16926

Male Inverted SAE 45° - Swivel - 90° Elbow

| #           |             |         |                |        |    |        |    |        |        |    |
|-------------|-------------|---------|----------------|--------|----|--------|----|--------|--------|----|
| Part Number | Thread inch |         | Hose I.D. inch | A inch | mm | E inch | mm | W inch | B inch | mm |
| 16926-4-4   | 1/4         | 7/16x24 | 3/16           | 2.27   | 58 | 1.56   | 40 | 7/16   | 1.40   | 36 |
| 16926-6-6   | 3/8         | 5/8x18  | 5/16           | 1.89   | 48 | 1.48   | 38 | 5/8    | 1.03   | 26 |
| 16926-8-8   | 1/2         | 3/4x18  | 13/32          | 2.25   | 57 | 1.88   | 48 | 3/4    | 1.39   | 35 |



**WARNING:** The products described in this catalog can expose you to chemicals, including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).




view on web page

## 1JC26

Female Seal-Lok® - Swivel - Short

| #           |             |            |                |        |    |        |    |        |        |        |    |
|-------------|-------------|------------|----------------|--------|----|--------|----|--------|--------|--------|----|
| Part Number | Thread inch |            | Hose I.D. inch | A inch | mm | C inch | mm | H inch | W inch | B inch | mm |
| 1JC26-4-4   | 1/4         | 9/16x18    | 3/16           | 1.66   | 42 | 0.31   | 8  | 9/16   | 11/16  | 0.79   | 20 |
| 1JC26-6-6   | 3/8         | 11/16x16   | 5/16           | 1.70   | 43 | 0.34   | 9  | 11/16  | 13/16  | 0.84   | 21 |
| 1JC26-8-8   | 1/2         | 13/16x16   | 13/32          | 1.76   | 45 | 0.43   | 11 | 13/16  | 15/16  | 0.90   | 23 |
| 1JC26-10-10 | 5/8         | 1x14       | 1/2            | 2.16   | 55 | 0.53   | 13 | 15/16  | 1-1/8  | 1.21   | 31 |
| 1JC26-12-12 | 3/4         | 1-3/16x12  | 5/8            | 2.13   | 54 | 0.55   | 14 | 1-1/8  | 1-3/8  | 1.19   | 30 |
| 1JC26-16-16 | 1           | 1-7/16x12  | 7/8            | 2.39   | 61 | 0.56   | 14 | 1-3/8  | 1-5/8  | 1.35   | 34 |
| 1JC26-20-20 | 1-1/4       | 1-11/16x12 | 1-1/8          | 2.45   | 62 | 0.59   | 15 | 1-7/8  | 1-7/8  | 1.39   | 35 |



view on web page

When measuring overall length to the end of the nut, B + C must be used to calculate cut-off allowance.

See Accessories Section for O-Rings.



**WARNING:** The products described in this catalog can expose you to chemicals, including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).