
3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
PILOT OPERATED

ANODIZED ALUMINIUM
NAMUR
SOLENOID OPERATED - SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
BSP	1 mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4"	8	1400	2	-	10	-25	55	NBR	**341N3290**	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7350
	8	1400	2	-	10	-25	75	NBR	**341N3290**	-	488660.01	0-20	Ex ia IIC T6	-	0.3 to 3	7.0	7350
	8	1400	2	-	10	-25	75	NBR	**341N3290**	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	7350
	8	1400	2	-	10	-25	65	NBR	**341N3296**	2995	482740	-	-	-	1.6	6.0/8.0	8029
	8	1400	2	10	10	-25	65	NBR	**341N3296**	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8029
	8	1400	2	-	10	-25	65	NBR	**341N3296**	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8029
	8	1400	2	-	10	-20	80	NBR	**341N3296**	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8029
	8	1400	2	-	10	-20	55	NBR	**341N3296**$_{2}$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8029
	8	1400	2	-	10	-25	65	NBR	**341N3297**$_{1}$	2995	482740	-	-	-	1.6	6.0/8.0	8029
	8	1400	2	10	10	-25	65	NBR	**341N3297**$_{1}$	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8029
	8	1400	2	-	10	-25	65	NBR	**341N3297**$_{1}$	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8029
	8	1400	2	-	10	-20	80	NBR	**341N3297**$_{1}$	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8029
	8	1400	2	-	10	-20	55	NBR	**341N3297**$_{12}$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8029
	7	1250	2.5	10	10	-10	50	NBR	**341N05**$_{1}$	-	496131	-	-	3	3	1.2	8162
	7	1250	2.5	10	10	-10	50	NBR	**341N05**$_{1}$	-	496482	-	-	3	3	1.2	8162
	7	1250	2.5	10	10	-10	50	NBR	**341N05**$_{1}$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8162

Notes:
1.With manual override
2. A minimum current of 65 mA is required with this coil configuration

INDEX FOR VALVES

Valve Reference	Page
322G3606	54
322G3610	98
322G37	54,86
322G3706	54
322G3710	98
322G38	54
322G3806	54
322G3810	98
322G39	54,86
322G3906	54
322G3910	98
322G40	54
322G4006	54
322G4010	98
322G75	52,84
322G7506	52,122
322H35	52
322H36	54
322H71	52
322H7106	52,122
322H73	52,122
322H7306	52,122
322H75	52,122
322H7506	52,122
322K4106	84
322K4306	84
322K4506	84
322K4606	84
322K4706	86
325K4106	56
325K4306	56
325K4506	56
325K4606	56
325K4706	56
E 331B01	202
331B02	210
331B0216	210
E 331B21	204
E 331B74	202
331B7490	202
E 331L21	206
331N03	304
331N04	304
331N34	306
E 332B01	204
332B02	204
E 332B21	206
E 341B01	246
341B02	244
E 341B21	246
341B34	244
341B3403	244
341B3440	244
341B3490	244
E 341F21	246
341F34	252
341F3403	252
341F3440	252
E 341L01	262
341L0197	262
E 341L02	260
341L04	262
341L05	262
341L11	258
E 341L1130	258
U 341L1130	258
E 341L21	254
341L2190	254
341L9101	250
341L9201	254
341L9504	330
341L9534	330
341L9594	332
341L9597	332
341L9598	332
341N01	308
341N02	314
U 341N0250	366
341N04	318
341N05	312
341N0502	314
341N11	308
341N12	316
341N21	308
341N2190	308
341N22	316
341N31	310
341N3102	310
341N3108	310
341N3128	310
341N3130	310
341N3190	310
341N3196	310
341N3197	310
341N32	316
341N3202	316
U 341N3250	364
341N3290	312
U 341N3292	364
U 341N3295	364
341N3297	312
341N34	318
341N35	314
341N3502	314
341P01	284
341P02	286
U 341P0250	358
341P03	286
341P04	290
341P21	284
341P2108	284
341P2190	286
341P2197	284
341P22	288
341P2290	288
341P2297	288
U 341P3250	358
U 341P3292	360
U 341P3295	360
341P33	286
341P34	290
342N03	326
342N11	326
342N3197	326
342N33	326
343N03	328
345B04	248
345B34	248
345F34	252
345L01	264
345L21	256
345N31	330
345P21	296
347L04	256
347L11	260
E 347L1130	260
347L9101	250
347L9201	256
347N03	322
347N04	324