5/2


316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

PILOT OPERATED

316L STAINLESS ST.

NAMUR

DUAL SOLENOIDS



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
	1			AC	DC									AC	DC		
	mm	Qn l/min	bar	bar	bar	°C	°C							W	W		
3/8"-1/4"NPT	8	1400	2	10	10	-25	80	NBR	U347N3250 [1]	4270	481000	-	-	8	8	2.1	7557
	8	1400	2	10	10	-25	80	NBR	U347N3250 [1]	2995	481865	-	-	8	9	2.1	7557

Notes:
1.Pilot seat in FKM

INDEX FOR VALVES

	Valve Reference	Page
	347N11	320
	347N12	322
	347N31	320
	347N3190	320
	347N3197	320
	347N32	322
U	347N3250	368
	347N33	322
	347N34	324
	347P01	292
	347P02	294
	347P03	294
	347P04	296
	347P21	292
	347P2190	292
	347P2197	292
	347P22	294
U	347P3250	362
U	347P3295	362
	347P33	294
	347P34	296
	421F35	58
U	441P3250	358
	443776W	70
	443777W	70
	443778W	70
	443779W	70
	443780W	70
	443781W	70
	443782W	70
	443783W	70
	443784W	92
	443785W	70
	443786W	70
	443787W	70

Valve Reference	Page
443788W	92
443789W	70
443790W	72
443791W	72
443792W	92
443793W	72
443794W	72
443795W	72
443796W	92
443797W	72
443798W	72
443799W	72
443800W	92
443801W	72
443802W	92
443803W	92
443804W	70
443805W	82
443806W	82
443807W	82
443808W	82
443809W	82
443810W	82
443811W	82
444492W	70
444494W	70
444497W	70
444499W	82
444500W	82
444501W	82
444502W	82
444503W	82
444513W	82
444576W	82
444600W	82

Valve Reference	Page
444601W	82
444602W	82
444603W	82
444604W	82
444605W	82
542N03	340
547N03	338