



15mm DIN Form C (8mm spacing) pilot solenoid valve

For use with 15mm pilot solenoid valve PVL-B2 body

Manual Overrides				Flush (Not Extended)		Extended	
Without Manual Override				Blue Override, non locking	Yellow Override, Locking	Blue Override, non locking	Yellow Override, Locking
	Voltage	W (g)	Order code	Order code	Order code	Order code	Order code
	12 Vdc	38	P2E-KV32B0	P2E-KV32B1	P2E-KV32B2	P2E-KV32B3	P2E-KV32B4
	24 Vdc	38	P2E-KV32C0	P2E-KV32C1	P2E-KV32C2	P2E-KV32C3	P2E-KV32C4
	48 Vdc	38	P2E-KV32D0	P2E-KV32D1	P2E-KV32D2	P2E-KV32D3	P2E-KV32D4
	24 Vac 50Hz	38	P2E-KV31C0	P2E-KV31C1	P2E-KV31C2	P2E-KV31C3	P2E-KV31C4
	48 Vac 50/60Hz	38	P2E-KV34D0	P2E-KV34D1	P2E-KV34D2	P2E-KV34D3	P2E-KV34D4
	115 Vac 50Hz	38	P2E-KV31F0	P2E-KV31F1	P2E-KV31F2	P2E-KV31F3	P2E-KV31F4
	120 Vac 60 Hz						
	230 Vac 50Hz		P2E-KV31J0	P2E-KV31J1	P2E-KV31J2	P2E-KV31J3	P2E-KV31J4
	240 Vac 60 Hz	38					

15 mm N.C. Solenoid Operator - Mobile version

Without Manual Override				Not Extended
				Blue Override non locking flush
	Voltage	W (g)	Order code	Order code
	12 Vdc	38	P2E-MV35B0	P2E-MV35B1
	24 Vdc	38	P2E-MV35C0	P2E-MV35C1
	37.5 Vdc	38	P2E-MV35W0	P2E-MV35W1
	48 Vdc	38	P2E-MV35D0	P2E-MV35D1
	72 Vdc	38	P2E-MV35T0	P2E-MV35T1
	78 Vdc	38	P2E-MV35Y0	P2E-MV35Y1
	96 Vdc	38	P2E-MV35V0	P2E-MV35V1
	110 Vdc	38	P2E-MV35E0	P2E-MV35E1

Suppressor and LED indicators


For 8 mm solenoid pin spacing -

For mounting between the solenoid valve and the cable plug

Description	Electrical voltage	W (g)	Order code
	24 VAC/DC	3	P8V-CR26C
	115 VAC 50 Hz	3	P8V-CR24F
	120 VAC 60 Hz		
	230 VAC 50 Hz 240 VAC 60 Hz	3	P8V-CR24J


Mounting screws included with the solenoid valve operator

15 mm N.C. Solenoid Operator - Food Industry version

Manual Overrides				Flush (Not Extended)		Extended	
Without Manual Override				Blue Override, non locking	Yellow Override, Locking	Blue Override, non locking	Yellow Override, Locking
	Voltage	W (g)	Order code	Order code	Order code	Order code	Order code
	24 Vdc	38	P2E-QV32C0	P2E-QV32C1	P2E-QV32C2	P2E-QV32C3	P2E-QV32C4
	48 Vdc	38	P2E-QV32D0	P2E-QV32D1	P2E-QV32D2		
	24 Vac 50 Hz	38	P2E-QV31C0	P2E-QV31C1	P2E-QV31C2	P2E-QV31C3	P2E-QV31C4
	48 Vac 50/60Hz	38	P2E-QV34D0	P2E-QV34D1	P2E-QV34D2		
	115 Vac 50Hz/ 120 Vac 60Hz	38	P2E-QV31F0	P2E-QV31F1	P2E-QV31F2	P2E-QV31F3	P2E-QV31F4
	230 Vac 50Hz						
	240 Vac 60Hz/	38	P2E-QV31J0	P2E-QV31J1	P2E-QV31J2	P2E-QV31J3	P2E-QV31J4

Mounting screws included with the solenoid valve operator

Solenoid Connectors 15 mm DIN Form C / ISO15217

	Description	Characteristic	Visualisation	Cable length	W (g)	Order code
 Connector schematic No LED version LED version 	With large headed screw suitable for mounting in inaccessible or recess position	Standard IP65	No LED	No cable	20	P8C-C
			24 Vdc LED	No cable	20	P8C-C26C
			110 Vac LED	No cable	20	P8C-C21E
	With standard screw	Standard IP65	No LED	No cable	15	P8C-D
				2 meters	115	P8L-C2
				5 meters	240	P8L-C5
			24 Vdc/Vac LED	No cable	15	P8C-D26C
				2 meters	170	P8L-C226C
				5 meters	240	P8L-C526C
				10 meters	440	P8L-CA26C
			110 Vac LED	No cable	115	P8C-D21E
				2 meters	115	P8L-C221E
				5 meters	230	P8L-C521E

In accordance with the EU Machine Directive, EN 983, solenoid valves with manual override should have spring-return operating arms for safety.