

Exhaust versions

0489

3/2 In-Line Threaded Exhaust Port Ball Valve, Female BSPP and Metric Thread

Nickel-plated brass, NBR



Scan for more dimensions



DN	C1	C	References
7	M5x0.8	G1/4	0489 07 13
10	M5x0.8	G3/8	0489 10 17
13	G1/8	G1/2	0489 13 21
18	G1/4	G3/4	0489 18 27
23	G1/4	G1	0489 23 34

Max. operating pressure: 40 bar

0449

3/2 Panel-Mountable In-Line Threaded Exhaust Port Ball Valve, Female BSPP and Metric Thread

Nickel-plated brass, NBR



Scan for more dimensions



DN	C1	C	References
7	M5x0.8	G1/4	0449 07 13
10	M5x0.8	G3/8	0449 10 17
13	G1/8	G1/2	0449 13 21

Max. operating pressure: 20 bar

0469

3/2 In-Line Vented Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR



Scan for more dimensions



DN	C	References
4	G1/8	0469 04 10
7	G1/4	0469 07 13
10	G3/8	0469 10 17
13	G1/2	0469 13 21
18	G3/4	0469 18 27
23	G1	0469 23 34

Max. operating pressure: 40 bar

0462

3/2 Right-Angled Ball Valve with Vent, Female BSPP Thread

Nickel-plated brass, NBR



Scan for more dimensions



DN	C	References
6	G1/8	0462 06 10
	G1/4	0462 06 13
9	G3/8	0462 09 17
12	G1/2	0462 12 21
18	G3/4	0462 18 27
23	G1	0462 23 34

Max. operating pressure: 20 bar

0461

3/2 Right-Angled Ball Valve with Vent, Male/Female BSPP Thread

Nickel-plated brass, NBR



Scan for more dimensions



DN	C	References
6	G1/8	0461 06 10
	G1/4	0461 06 13
9	G3/8	0461 09 17
12	G1/2	0461 12 21
18	G3/4	0461 18 27

Max. operating pressure: 20 bar