

3675

Stud Fitting, Male BSPT Thread

Chemical Nickel-plated brass, FKM



Scan for more dimensions



ØD	C	References
4	R1/8	3675 04 10
	R1/4	3675 04 13
6	R1/8	3675 06 10
	R1/4	3675 06 13
8	R1/8	3675 08 10
	R1/4	3675 08 13
10	R3/8	3675 10 17
	R1/2	3675 10 21
12	R1/4	3675 12 13
	R3/8	3675 12 17
14	R1/2	3675 14 21
	R3/8	3675 14 17

3601

Stud Fitting, Male BSPP and Metric Thread

Chemical Nickel-plated brass, FKM



Scan for more dimensions



ØD	C	References
4	M5x0.8	3601 04 19
	M6x1	3601 04 52
	M8x1	3601 04 56
	G1/8	3601 04 10
6	G1/4	3601 04 13
	M5x0.8	3601 06 19
	M10x1	3601 06 60
	G1/8	3601 06 10
8	G1/4	3601 06 13
	G1/8	3601 08 10
	G1/4	3601 08 13
	G3/8	3601 08 17
10	G1/4	3601 10 13
	G3/8	3601 10 17
	G1/2	3601 10 21
	G1/4	3601 12 13
12	G3/8	3601 12 17
	G1/2	3601 12 21
	G3/8	3601 14 17
	G1/2	3601 14 21

3681

Stud Fitting with Internal Hexagon, Male Metric Thread

Chemical Nickel-plated brass, FKM



Scan for more dimensions



ØD	C	References
4	M5x0.8	3681 04 19

3614

Stud Fitting, Female BSPP and Metric Thread

Chemical Nickel-plated brass, FKM



Scan for more dimensions



ØD	C	References
4	M5x0.8	3614 04 19
	G1/8	3614 04 10
	G1/4	3614 04 13
6	G1/8	3614 06 10
	G1/4	3614 06 13
8	G1/8	3614 08 10
	G1/4	3614 08 13
10	G3/8	3614 10 17
	G3/8	3614 12 17
12	G1/2	3614 12 21

3609

Stud Elbow, Male BSPT Thread

Chemical Nickel-plated brass, FKM



Scan for more dimensions



ØD	C	References
4	R1/8	3609 04 10
	R1/4	3609 04 13
6	R1/8	3609 06 10
	R1/4	3609 06 13
8	R1/8	3609 08 10
	R1/4	3609 08 13
10	R3/8	3609 10 17
	R1/2	3609 10 21
12	R1/4	3609 12 13
	R3/8	3609 12 17
14	R1/2	3609 14 21
	R3/8	3609 14 17

The body swivels for positioning purposes. Maximum pressure: 20 bar

3699

Compact Elbow, Male BSPP and Metric Thread

Chemical Nickel-plated brass, FKM



Scan for more dimensions



ØD	C	References
4	M5x0.8	3699 04 19
	M6x1	3699 04 52
	M8x1	3699 04 56
	G1/8	3699 04 10
6	G1/4	3699 04 13
	M10x1	3699 06 60
	G1/8	3699 06 10
	G1/4	3699 06 13
8	G1/8	3699 08 10
	G1/4	3699 08 13
	G3/8	3699 08 17
	G1/4	3699 10 13
10	G3/8	3699 10 17
	G1/4	3699 12 13
	G3/8	3699 12 17
	G1/2	3699 12 21
14	G3/8	3699 14 17
	G1/2	3699 14 21

The body swivels for positioning purposes. Maximum pressure: 20 bar

3618

Single Banjo, Male BSPP and Metric Thread

Chemical Nickel-plated brass, FKM



Scan for more dimensions



ØD	C	References
4	M5x0.8	3618 04 19
	G1/8	3618 04 10
6	M5x0.8	3618 06 19
	G1/8	3618 06 10
8	G1/4	3618 06 13
	G1/8	3618 08 10
10	G1/4	3618 08 13
	G3/8	3618 10 17

Maximum temperature: +80°C