


Brass Compression Fittings / Stud Fittings

0114 Stud Fitting, Female BSPP Thread


Brass



ØD	C		E	F	F1	H max	H1	Kg
4	G1/8	0114 04 10	9.5	14	10	26	16.5	0.020
	G1/4	0114 04 13	13.5	17	10	30	20.5	0.030
5	G1/8	0114 05 10	9.5	14	12	28	17	0.024
	G1/4	0114 05 13	13.5	17	12	31	21	0.032
6	G1/8	0114 06 10	9.5	14	13	28	17	0.025
	G1/4	0114 06 13	13.5	17	13	32	21	0.034
8	G1/8	0114 08 10	14	22	13	32	21.5	0.051
	G1/4	0114 08 13	9.5	14	14	29	16.5	0.026
10	G3/8	0114 08 17	13.5	17	14	33	20.5	0.035
	G1/2	0114 08 21	14	22	14	34	21	0.052
12	G3/8	0114 10 13	13.5	17	19	37	21.5	0.052
	G1/2	0114 10 17	14	22	19	37	22	0.069
14	G3/8	0114 10 17	18.5	27	19	42	26.5	0.099
	G1/2	0114 12 13	13.5	19	22	36	20.5	0.068
16	G3/8	0114 12 17	14	22	22	37	22	0.078
	G1/2	0114 12 21	18.5	27	22	42	26.5	0.109
18	G3/8	0114 14 13	13.5	22	24	36	18.5	0.084
	G1/2	0114 14 17	14	22	24	38	21	0.081
20	G3/8	0114 14 17	18.5	27	24	43	25.5	0.111
	G1/2	0114 15 17	14	22	24	38	21	0.077
22	G3/8	0114 15 21	18.5	27	24	43	25.5	0.109
	G1/2	0114 16 13	13.5	24	27	36	18	0.109
24	G3/8	0114 16 17	14	24	27	38	20.5	0.108
	G1/2	0114 16 21	18.5	27	27	44	26	0.129
26	G3/8	0114 18 17	14	27	30	39	19.5	0.141
	G1/2	0114 18 21	18.5	27	30	45	26	0.146
28	G3/4	0114 18 27	19.5	32	30	46	27	0.165
	G1/2	0114 20 21	18.5	30	32	44.5	24	0.173
30	G3/4	0114 20 27	19.5	32	32	47	26.5	0.174
	G1/2	0114 22 27	19.5	32	36	48	26.5	0.204

0109 Stud Elbow, Male BSPT Thread

Brass




ØD	C		F	H	J	L max	L1	Kg
4	R1/8	0109 04 10	10	17	8	19	9.5	0.016
	R1/4	0109 04 13	10	20	10	19	11	0.025
5	R1/8	0109 05 10	12	17.5	8	21	11	0.019
	R1/4	0109 05 13	12	21.5	10	22	12	0.029
6	R1/8	0109 06 10	13	18	8	22	11	0.021
	R1/4	0109 06 13	13	21.5	10	22	12	0.030
8	R1/8	0109 08 10	14	18.5	10	28	15	0.028
	R1/4	0109 08 13	14	22	10	28	15	0.033
10	R3/8	0109 08 17	14	24	12	28	15	0.044
	R1/2	0109 10 13	19	25	12	30	14.5	0.053
12	R3/8	0109 10 17	19	25.5	12	30	14.5	0.059
	R1/2	0109 10 21	19	32	19	36	21	0.108
14	R3/8	0109 12 13	22	26	15	30	15	0.073
	R1/2	0109 12 17	22	27	15	30	15	0.077
16	R3/8	0109 12 21	22	32	19	36	21	0.114
	R1/2	0109 14 17	24	30	19	35	18	0.104
18	R3/8	0109 14 21	24	32	19	35	18	0.112
	R1/2	0109 15 17	24	30	19	35	18	0.101
20	R3/8	0109 15 21	24	32	19	35	18	0.107
	R1/2	0109 16 17	27	30	19	39	21	0.122
22	R3/8	0109 16 21	27	33.5	19	39	21	0.132
	R1/2	0109 16 27	27	36.5	23	41	23	0.189
24	R3/8	0109 18 21	30	35.5	23	41	21.5	0.181
	R1/2	0109 18 27	30	36.5	23	41	21.5	0.197
26	R3/8	0109 20 21	32	36.5	23	42	21.5	0.186
	R1/2	0109 20 27	32	38	23	42	21.5	0.203
28	R3/4	0109 22 27	36	40	27	50	30	0.293
	R1	0109 22 34	36	44	27	50	30	0.332
30	R3/4	0109 25 34	41	44	27	54	30	0.370
	R1	0109 28 34	42	48	32	54	30	0.378

Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.

0109 Stud Elbow, Male NPT Thread

Brass



ØD	C		F	H	J	L max	L1	Kg
6	NPT1/8	0109 06 11	13	18	8	22	11	0.021
	NPT1/4	0109 06 14	13	21.5	10	22	12	0.030
8	NPT1/8	0109 08 11	14	18.5	10	28	15	0.027
	NPT1/4	0109 08 14	14	22	10	28	15	0.032
10	NPT1/4	0109 10 14	19	25	12	30	14.5	0.054