

Nickel-Plated Brass Adaptors

0900 Equal and Unequal Adaptor, Male BSPT Thread

Nickel-plated brass



C1	C2		F	L	Kg
	R1/8	0900 00 10	12	20.5	0.009
R1/8	R1/4	0900 10 13	14	24	0.014
	R3/8	0900 10 17	17	24.5	0.020
	R1/4	0900 00 13	14	27	0.017
R1/4	R3/8	0900 13 17	17	27.5	0.026
	R1/2	0900 13 21	22	30.5	0.046
R3/8	R3/8	0900 00 17	17	28	0.025
	R1/2	0900 17 21	22	31	0.046
R1/2	R1/2	0900 00 21	22	33.5	0.042
	R3/4	0900 21 27	27	37	0.084
R3/4	R3/4	0900 00 27	27	39.5	0.079
	R1	0900 27 34	34	42.5	0.145
R1	R1	0900 00 34	34	45.5	0.153

0901 Equal and Unequal Adaptor, Male BSPP and Metric Thread

Nickel-plated brass



C1	C2		E	E1	F	L	Kg
M5x0.8	M5x0.8	0901 00 19	4	4	8	11.5	0.002
	G1/8	0901 19 10	4	6	14	14.5	0.008
G1/8	G1/8	0901 00 10	6	6	14	16.5	0.009
	G1/4	0901 10 13	6	8	17	19	0.016
	G1/4	0901 00 13	8	8	17	21	0.019
G1/4	G3/8	0901 13 17	8	9	19	22	0.023
	G1/2	0901 13 21	8	10	24	23.5	0.036
G3/8	G3/8	0901 00 17	9	9	19	23	0.025
	G1/2	0901 17 21	9	10	24	24.5	0.038
G1/2	G1/2	0901 00 21	10	10	24	25.5	0.040

0192 Unequal Straight Adaptor, Male BSPT/BSPP Thread


Nickel-plated brass



C1	C2		E	F	L	Kg
R1/8	G1/4	0192 10 13	9.5	17	23.5	0.019
R1/4	G1/4	0192 13 13	9.5	17	27.5	0.024
R1/4	G1/2	0192 13 21	11	27	31.5	0.066
R3/8	G1/4	0192 17 13	9.5	17	28	0.025
R3/8	G1/2	0192 17 21	11	27	31.5	0.060
R1/2	G1/2	0192 21 21	11	27	34	0.061

0191 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread


Nickel-plated brass



ØD	ØD1	C		E	F	K	L	Kg
4	6	G1/4	0191 04 13	9.5	17	5	22.5	0.019
7	9	G1/4	0191 07 13	9.5	17	5	22.5	0.022
	9	G1/2	0191 07 21	11	27	7	29.5	0.058
10	12.2	G1/4	0191 10 13	9.5	17	5	22.5	0.020
	12.2	G1/2	0191 10 21	11	27	7	29.5	0.060
13	15.2	G1/4	0191 13 13	9.5	17	5	22.5	0.022
	15.2	G1/2	0191 13 21	11	27	7	29.5	0.059
16	18.5	G1/2	0191 16 21	11	27	7	36.5	0.067

0931 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

Nickel-plated brass



ØD	ØD1	C		E	F	K	L	Kg
6	7,3	G1/8	0931 06 10	6	12	4.5	19	0.009
	7,3	G1/4	0931 06 13	8	14	5	19	0.013
	8,3	G1/8	0931 07 10	6	12	4	19	0.009
7	8,3	G1/4	0931 07 13	8	14	5	19	0.014
	8,3	G3/8	0931 07 17	9	19	5	19	0.021
	9,3	G1/8	0931 08 10	6	12	4	19	0.009
8/9	9,3	G1/4	0931 08 13	8	14	5	19	0.014
	9,3	G3/8	0931 08 17	9	19	5	19	0.022
	12,5	G1/4	0931 10 13	8	14	5	19	0.016
10	12,5	G3/8	0931 10 17	9	19	5	19	0.024
	12,5	G1/2	0931 10 21	10	22	6	20	0.031
13	14,5	G1/4	0931 13 13	8	17	5	24	0.025
	14,5	G3/8	0931 13 17	9	19	5	24	0.036
	14,5	G1/2	0931 13 21	10	24	6	24	0.044
15/16	17,5	G3/8	0931 15 17	9	19	6	24	0.030
	17,5	G1/2	0931 15 21	10	22	6	24	0.036
18	20,6	G1/2	0931 18 21	10	22	6	24	0.040
19/20	20,6	G3/4	0931 20 27	12.5	32	8	36	0.101

Complementary Products

PVC braided Hoses
1025V**C04 - page 416

Clips
0697* - Page 421

When used with PVC braided hose, we recommend to add 1 clip at each end

