




Robust brass coupling with Japanese industrial profile. Coupling system with single-hand operation. Above average flow volumes and structure resistant to the effects of external forces.

- Available on request:
 - in brass material with nickel plating
 - with additional end connections
 - other seals for different temperature ranges and fluids



Japanese Profile

KA Single Shut-Off

Working Pressure*:
up to 35 bar

Material:


- Coupling: Brass
- Plug: Nickel plated steel
- Seals: NBR

Working Temperature:
-20°C up to +100°C (NBR)

Flow Rate Air:
1.150 l/min.
inlet pressure 6 bar, pressure drop 0.5 bar

Flow Rate Water:
16 l/min.
pressure drop 0.5 bar

* maximum static working pressure with design factor 4 to 1.




Single Shut-Off



Single Shut-Off

13KAAK Coupler with valve, Male Thread


Brass, NBR



A	HEX	L	L1	D
R1/4 13KAAK13MPX	22	49	12	27
R3/8 13KAAK17MPX	22	49	12	27
R1/2 13KAAK21MPX	22	53	17	27

13KATF Coupler with valve, Hose Barb


Brass, NBR



A	HEX	L	L1	D
6 13KATF06MPX	21	62	25	27
8 13KATF08MPX	21	62	25	27
10 13KATF10MPX	21	62	25	27
13 13KATF13MPX	21	62	25	27

13KAIW Coupler with valve, Female Thread

Brass, NBR



A	HEX	L	L1	D
G1/4 13KAIW13MPX	22	45	9	27
G3/8 13KAIW17MPX	22	45	9	27
G1/2 13KAIW21MPX	24	48	12	27