




ISO 5599-1 Sizes 1, 2 & 3

CNOMO operator with 30 x 30 DIN Form A / 24 Vdc / 2,7 W solenoid




With non locking manual override on solenoid valve operator - Without direct valve spool manual override

	Symbol	Description	Size	Weight (g)	Order code
		5/2 Single solenoid - Spring return	1 - 43 mm	500	DX1-621-BL49
			2 - 56 mm	750	DX2-621-BL49
			3 - 71 mm	1250	DX3-621-BL49
		5/2 Single solenoid - Differential	1 - 43 mm	500	DX1-651-BL49
			2 - 56 mm	750	DX2-651-BL49
			3 - 71 mm	1250	DX3-651-BL49
		5/2 Double solenoid	1 - 43 mm	650	DX1-606-BL49
			2 - 56 mm	900	DX2-606-BL49
			3 - 71 mm	1400	DX3-606-BL49
		5/3 Closed Center	1 - 43 mm	560	DX1-616-BL49
			2 - 56 mm	900	DX2-616-BL49
			3 - 71 mm	1400	DX3-616-BL49
		5/3 Vented Center	1 - 43 mm	650	DX1-611-BL49
			2 - 56 mm	900	DX2-611-BL49
			3 - 71 mm	1400	DX3-611-BL49
		5/3 Pressurised Center	1 - 43 mm	650	DX1-613-BL49
			2 - 56 mm	900	DX2-613-BL49

Solenoid connectors & cable plug to be ordered separately. See solenoid section

CNOMO operator without coil

With non locking manual override on solenoid valve operator - Without direct valve spool manual override

	Symbol	Description	Size	Weight (g)	Order code
		5/2 Single solenoid - Spring return	1 - 43 mm	400	DX1-621-BN
			2 - 56 mm	650	DX2-621-BN
			3 - 71 mm	1150	DX3-621-BN
		5/2 Single solenoid - Differential	1 - 43 mm	400	DX1-651-BN
			2 - 56 mm	650	DX2-651-BN
			3 - 71 mm	1150	DX3-651-BN
		5/2 Double solenoid	1 - 43 mm	550	DX1-606-BN
			2 - 56 mm	800	DX2-606-BN
			3 - 71 mm	1300	DX3-606-BN
		5/3 Closed Center	1 - 43 mm	550	DX1-616-BN
			2 - 56 mm	800	DX2-616-BN
			3 - 71 mm	1300	DX3-616-BN
		5/3 Vented Center	1 - 43 mm	550	DX1-611-BN
			2 - 56 mm	800	DX2-611-BN
			3 - 71 mm	1300	DX3-611-BN
		5/3 Pressurised Center	1 - 43 mm	550	DX1-613-BN
			2 - 56 mm	800	DX2-613-BN

30 x 30 DIN Form A or 22 x 30 DIN Form B coil & coil connectors to be ordered separately. See solenoid section