

Maintenance components

	Valve pilot	Connection	Weight (g)	Order code	
 P2D8V32C5  P2D2W3226C5  P2M2K0PA	Solenoid pilot	M8 - 3 Pins - IP67	15	P2D8V32C5	
		Clip connector - 2 pins - IP40 With LED and voltage surge suppression	15	P2D2W3226C5	
	Pneumatic pilot	4 mm OD tubing push-in elbow fitting	10	P2M2K0PA	
	size 1 valve modules without solenoid pilot and without sub-base		Weight (g)	Order code	
 P2M1X4EE	4/2	monostable	26	P2M1X4ES	
		bistable	25	P2M1X4EE	
	3/2	double NC + NC	28	P2M1XDEE	
		double NO + NO	28	P2M1XCEE	
		double NC + NO	28	P2M1XEEE	
		single NC	25	P2M1X3ES	
	4/3 CE		double 3/2 NC + NC without exhaust check valve	28	P2M1XGEE
	size 2 valve modules without solenoid pilot and without sub-base		Weight (g)	Order code	
 P2M2X4EE	4/2	monostable	28	P2M2X4ES	
		bistable	30	P2M2X4EE	
	3/2	double NC + NC	32	P2M2XDEE	
		double NO + NO	32	P2M2XCEE	
		double NC + NO	32	P2M2XEEE	
		single NC	28	P2M2X3ES	
	4/3 CE		double 3/2 NC + NC without exhaust check valve	32	P2M2XGEE
	Set of maintenance parts		Weight (g)	Order code	
  	Seals	Set of various seals: 3 under solenoid pilot seals 3 inter island base seals 2 for dual 4/2 valves (2 parts) 2 for single and dual 3/2 – Size 1 – valves 2 for single 4/2 – Size 1 – valves 2 for size 2 valves (all functions)	8	P2M2K0JA	
	Fitting locking clips	Set of 14 clips: 4 for dual 4/2 valves 6 for size 1 valves 2 for size 2 valves 2 for intermediate supply modules	10	P2M2K0CA	
	Manual override forks	Set of 10 isolating forks for pilot solenoid manual override	8	P2M2K0FA	