
2/2 HIGH CORROSION RESISTANT VALVES V SERIES DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED




Port size	Orifice Ø	Flow factor			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
					Min			Min	Max										
	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4" NPT	0.8	-	-	20	0	-	200	-25	65	PUR	U121VS3750A [1]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2	8165
	0.8	-	-	20	0	-	200	-25	75	PUR	U121VS3750A [1]	-	492210	1-21	Ex eb mb IIC T5 to T6	-	1 to 1.8	9.0/10.1/10.2	6713
	0.8	-	-	20	0	200	200	-25	75	PUR	U121VS3750A [1]	-	492310	1-21	Ex mb II T4 to T5	6	6	9.0/10.1/10.2	6713
	0.8	-	-	20	0	200	200	-25	65	PUR	U121VS3750A [1]	-	496560	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	0.8	-	-	20	0	200	200	-25	65	PUR	U121VS3750A [1]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	-	98	-40	75	PUR	U121V5595 [23]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	-	98	-40	75	PUR	U121V5595 [23]	-	492210	1-21	Ex eb mb IIC T5 to T6	-	1 to 1.8	9.0/10.1/10.2	6713
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V5595 [23]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	98	98	-40	75	PUR	U121V5595 [23]	-	492310	1-21	Ex mb II T4 to T5	6	6	9.0/10.1/10.2	6713
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V5595 [23]	-	496560	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	98	98	-40	50	PUR	U121V5595 [23]	-	496895	-	-	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	-	98	-40	65	PUR	U121V7595 [3]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2/10.3	8165
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V7595 [3]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2/10.3	8165
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V7595 [3]	-	497105	1-21	Ex db IIC T4 to T6	8	8	9.0/10.1/10.2/10.3	8299
	1	0.6	0.04	40	0	98	98	-40	50	PUR	U121V7595 [3]	-	496895	-	-	8	8	9.0/10.1/10.2/10.3	8165

Notes:
1. Valve only compatible with neutral gases
2. Valve delivered with an individual material traceability certificate (2.2 following EN10204)
3. Valve compatible with water only up to 40°C

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max								
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	1.5	1.5	1.4	1.4	0.08	0.08	0	16	16	-10	120	FKM	132K04	4270	481000	8	8	2.1	3510
	1.5	1.5	1.4	1.4	0.08	0.08	0	16	16	-10	100	FKM	132K04	2995	481865	8	9	2.1	3510
	2	2	1.8	1.8	0.11	0.11	0	10	10	-10	120	FKM	132K06	4270	481000	8	8	2.1	3510
	2	2	1.8	1.8	0.11	0.11	0	10	10	-10	100	FKM	132K06	2995	481865	8	9	2.1	3510
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T23	4270	481000	8	8	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T23	2995	481865	8	9	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	-	10	-10	75	FKM	132T23	4270	486265	-	14	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T2301 [1]	4270	481000	8	8	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T2301 [1]	2995	481865	8	9	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	-	10	-10	75	FKM	132T2301 [1]	4270	486265	-	14	2.0	3223
	2.5	2.5	2.2	2.2	0.13	0.13	0	7	7	-10	120	FKM	132K03	4270	481000	8	8	2.1	3510
	2.5	2.5	2.2	2.2	0.13	0.13	0	7	7	-10	100	FKM	132K03	2995	481865	8	9	2.1	3510
	3	4	4.5	6	0.27	0.36	0	10	-	-10	75	FKM	132T22	4270	481044	14	-	2.2	3223
	3	4	4.5	6	0.27	0.36	0	7	-	-10	75	FKM	132T22	2995	492425	14	-	2.2	3223

Notes:
1.With manual override

INDEX BY VALVE REFERENCE

Valve Reference	Page
E 131E03	178,274
U 033X0111	298
U 033X5156	370
U 033X5195	374
U 033X5256	376
U 033X7759	372
121F2523	158
E 121F43	30,116
E 121F4302	30,68
E 121F44	30,116
E 121F4406	30,68
121F4417	30
121F47	30
121F4706	30,116
121F63	30,116
121F64	30,116
121F67	30,116
121FH0015	138
121FH0020	138
121FH0025	138
121FH0030	138
121FH1015	138
121FH1020	138
121FH1025	138
121FH1030	138
121G2520	156
121G2523	156
121K01	24,62
121K0103	102
121K0150	24,62
121K02	24,62
121K0250	24,62
E 121K03	24,112
E 121K0302	24,62
121K0323	102
E 121K0352	24,62
121K0397	24
E 121K04	22,112
E 121K0402	22,62
121K0497	22
E 121K07	22
121K0706	22,62
121K1302	22
E 121K14	22,112
E 121K23	22,112
121K2423	156
121K3106	26,64,114
121K3206	26,64,114
121K3303	102
121K3306	26,64,114
121K3321	156
E 121K45	26,64
E 121K4503	102
E 121K46	26,64
E 121K4603	102
121K6220	156
E 121K63	24,112
E 121K64	24,112
121K6423	156
E 121K65	22,112
E 121K67	22,112
121KH0015	138
121KH0020	138
121KH0025	138
121KH0030	138
121KH1015	138
121KH1020	138
121KH1025	138
121KH1030	138
121KH1040	138
121KH1050	138
121M13	22,62
121M14	22,62
121V5106	130
121V5112	130
121V5163	104,130
121V5206	130
121V5212	130
121V5263	104,130
121V5306	128
121V5363	104,128
121V5397	130
121V5406	128
121V5463	104,128
121V5497	128
U 121V5595	148
121V5706	128
121V5763	104,128
U 121V7595	148
U 121VS3750A	148
121ZH0010	136
121ZH0015	136
121ZH0020	136
121ZH0025	136
121ZH0030	136
121ZH1010	136
121ZH1015	136
121ZH1020	136
121ZH1025	136
121ZH1030	136
122F44	32
122K83	28
122K8306	28,64
122K8321	156,114
122K84	28,114
122K8406	28,114
122K9321	158
122K9363	28,114
122V8306	132
125K01	28,66
125K03	28
131B04	192
131B14	192
E 131F26	196
E 131F43	188
E 131F4350	188
131F4397	280
E 131F44	188
131F4410	186
E 131F4450	188
131F4490	186
131F46	188
131F4650	188
U 131F5295	354
131F5406	194
U 131F7695	354
131FH0315	226
131FH0320	226
131FH0325	226
131FH0330	226
131FH1115	226
131FH1120	226
131FH1125	226
131FH1130	226
131FH1315	226
131FH1320	226
131FH1325	226
131FH1330	226
E 131K03	178
E 131K0308	178,274

INDEX BY VALVE REFERENCE

	Valve Reference	Page
E	131K0350	178,274
E	131K0358	176,270
	131K0397	176
E	131K04	174,272
E	131K0450	174,272
	131K0490	172,270
	131K0497	174,270
E	131K06	176,272
	131K0648	240
E	131K0650	176,272
E	131K13	172
E	131K14	172
	131K16	172
	131K1650	172
E	131K63	178
E	131K6350	178
E	131K64	174
E	131K6450	174
	131KH0115	224
	131KH0120	224
	131KH0125	224
	131KH0130	224
	131KH1115	224
	131KH1120	224
	131KH1125	224
	131KH1130	224
	131KH1140	224
	131KH1150	224
	131M14	172,270
	131M15	172,270
	131M74	186
	131M7450	186
	131M75	186
	131M7550	186
	131T21	178
	131T2101	274
	131T22	178
	131T23	174
	131T2301	174
	131T29	176
	131T2901	176
	131V5306	214
	131V5363	214
	131V5397	214
	131V5406	214
	131V5463	214
	131V5490	214
	131V5497	214
	131X1101	302
U	131X1101	302
	131X1131	302
U	131X1201	356
	131ZH0125	222
	131ZH0130	222
	131ZH0315	222
	131ZH0320	222
	131ZH0325	222
	131ZH0330	222
	131ZH1115	222
	131ZH1120	222
	131ZH1125	222
	131ZH1130	222
	131ZH1315	222
	131ZH1320	222
	131ZH1325	222
	131ZH1330	222
	132F43	188
	132F44	188
	132F46	188
	132K03	180
	132K04	180
	132K06	180
	132T22	180
	132T23	180
	132T2301	178
	132T29	180
	133F4650	280
E	133K03	182
E	133K0350	182
E	133K04	182
E	133K0450	182
	133K0497	182
E	133K05	182
E	133K06	182
E	133K0650	182
E	133K13	182
E	133K14	182
E	133K16	182
	133T21	182
	133T2101	184
	133T23	182
	133T2301	182
	133V5306	216
	133V5363	216
	133V5406	216
	133V5463	216
U	133V5595	344
U	133V5695	344
U	133V7595	344
U	133V7695	344
	133X01	282
U	133X01	282
U	133X0111	276
U	133X5156	346
U	133X5195	354
U	133X5196	346
U	133X5296	352
U	133X7195	356
U	133X7709	348
U	133X77591	348
	135K03	278
	135K04	184
	2019F1GRG7	140
	2019F1GVG7	140
	2019F1JRG7	140
	2019F1JVG7	140
	2019F1LRG7	140
	2019F1LVG7	140
	2019F1NRG7	140
	2019F1NVG7	140
	2019F1QEG7	140
	2019F1QVG7	140
	2019F1SEG7	140
	2019F1SVG7	140
	201LG1GVG2	144
	201LG1JVG2	144
	201LG1LVG2	144
	201LG2GVG2	144
	201LG2JVG2	144
	201LG2LVG2	144
	201LG2NVG7	144
	201LG3SVG7	144
	201LG3UVG7	144
	201LG4SVG6	144
	201LG4UVG7	144
	202LG2NVG7	146
	202LG2SVG7	146
	202LG4SVG7	146
	202LG4UVG7	146
	221G13	34